

**Amendments to the Claims:**

This listing of claims will replace all prior versions, and listings, of claims in the application:

**Listing of Claims:**

1. (Previously Presented) A method of configuring a hard copy output engine comprising:

receiving an electronic message including hard copy output engine configuration data from an undesignated website through a firewall, wherein the electronic message transmitted through the firewall designates a hardcopy output engine to be configured; and

configuring the hard copy output engine using the hard copy output engine configuration data, wherein receiving the electronic message comprises receiving an email at the hard copy output engine and wherein configuring comprises configuring the hard copy output engine via an embedded web server contained in the hard copy output engine using the hard copy output engine configuration data.

2. (Canceled)

3. (Canceled)

4. (Canceled)

5. (Original) The method of claim 1, wherein receiving the electronic message comprises receiving an XML script and configuring includes setting a threshold for an element chosen from a group consisting of: pigmentation material, marking material, number of hours of operation and number of sheets of print media consumed.

6. (Original) The method of claim 1, wherein the hard copy output engine is chosen from a group consisting of: facsimile machines, photocopiers and printers.

7. (Original) The method of claim 1, wherein the configuration data include data prepared by:

- determining a make and model for the hard copy output engine;
- determining a serial number for the hard copy output engine; and
- determining user thresholds for consumables associated with the hard copy output engine.

8. (Previously Presented) An apparatus comprising:  
a device configured to provide a computer instruction signal embodied in a carrier wave carrying instructions that when executed by a processor cause the processor to:

- receive an electronic message including hard copy output engine configuration data from an undesignated website through a firewall; and
- configure the hard copy output engine using the configuration data,

wherein the computer instruction signal embodied in the carrier wave carrying instructions that cause the processor to receive an electronic message includes a computer instruction signal embodied in the carrier wave carrying instructions that cause the processor to receive an email at the hard copy output engine, and wherein the computer instruction signal embodied in the carrier wave carrying instructions that cause the processor to configure comprises a computer instruction signal embodied in the carrier wave carrying instructions that cause the processor to configure the hard copy output engine via an embedded web server contained in the hard copy output engine using the configuration data.

9. (Canceled)

10. (Previously Presented) The apparatus of claim 8, wherein the computer instruction signal embodied in the carrier wave carrying instructions that cause the processor to receive an electronic message includes a computer instruction signal embodied in the carrier wave carrying instructions that cause the processor to receive an email through the firewall.

11. (Previously Presented) The apparatus of claim 8, wherein the computer instruction signal embodied in the carrier wave carrying instructions that cause the processor to receive an electronic message includes a computer instruction signal embodied in the carrier wave carrying instructions that cause the processor to:

receive an email through the firewall at a first user station; and  
forward the email to the hard copy output engine.

12. (Previously Presented) The apparatus of claim 8, wherein the computer instruction signal embodied in the carrier wave carrying instructions that cause the processor to cause the processor to configure the hard copy output engine includes a computer instruction signal embodied in the carrier wave carrying instructions that cause the processor to configure the hard copy output engine via the embedded web server to set a threshold for an element chosen from a group consisting of: pigmentation material, marking material, number of hours of operation and number of sheets of print media consumed.

13. (Previously Presented) The apparatus of claim 8, wherein the computer instruction signal embodied in the carrier wave carrying instructions that cause the processor to receive an electronic message includes a computer instruction signal embodied in the carrier wave carrying instructions that cause the processor to receive an XML script, and wherein the computer instruction signal embodied in the carrier wave carrying instructions that cause the processor to configure the hard copy output engine includes a computer instruction signal embodied in the carrier wave carrying instructions that cause the processor to configure a hard copy output engine chosen from a group consisting of: facsimile machines, photocopiers and printers.

14. (Currently Amended) A computer implemented control system for a hard copy output engine, the system comprising:

memory configured to store a software module; and  
processing circuitry configured to employ the software module to:

receive an electronic message including hard copy output engine configuration data from an undesignated website through a firewall; and  
configure the hard copy output engine using the configuration data, wherein the processing circuitry configured to employ the software module to receive an electronic message comprises processing circuitry configured to:  
receive an email through the firewall at a first user station; and  
forward the email to the hard copy output engine, wherein the processing circuitry configured to employ the software module to configure the hard copy output engine comprises processing circuitry configured to employ the software module to configure the hard copy output engine via an embedded web server contained in the hard copy output engine to set a threshold for an element chosen from a group consisting of: pigmentation material, marking material, number of hours of operation and number of sheets of print media consumed.

15. (Original) The computer implemented control system of claim 14, wherein the processing circuitry configured to employ the software module to receive an electronic message comprises processing circuitry configured to employ the software module to receive an email at the hard copy output engine, and wherein the processing circuitry configured to employ the software module to configure the hard copy output engine comprises processing circuitry configured to employ the software module to configure the hard copy output engine via an embedded web server contained in the hard copy output engine.

16. (Previously Presented) The computer implemented control system of claim 14, wherein the processing circuitry configured to employ the software module to receive an electronic message comprises processing circuitry configured to employ the software module to receive an email through the firewall.

17. (Canceled)

18. (Original) The computer implemented control system of claim 14, wherein the processing circuitry configured to receive an electronic message

comprises processing circuitry configured to employ the software module to receive an XML script.

19. (Original) The computer implemented control system of claim 14, wherein the hard copy output engine is chosen from a group consisting of: facsimile machines, photocopiers and printers.

20. (Canceled)

21. (Canceled)

22. (Canceled)

23. (Canceled)

24. (Canceled)

25. (Canceled.

26. (Canceled)

27. (Currently Amended) A method comprising:  
forming hard copy output engine configuration data on a first side of a firewall based upon input received from a second side of the firewall; and  
transmitting an electronic message including the configuration data through the firewall to a hard copy output engine on the second side of the firewall;  
and  
providing the input from the second side of the firewall to the first side of the firewall, wherein the step of providing the input comprises interacting with a website on the first side of the firewall with a web browser on the second side of the firewall.

28. (Previously Presented) The method of claim 27, wherein the electronic message comprises an email.

29. (Previously Presented) The method of claim 27, wherein transmitting the electronic message comprises:

transmitting the electronic message to a user station; and  
forwarding the electronic message to the hard copy output engine.

30. (Previously Presented) The method of claim 27 further comprising configuring the hard copy output engine using the configuration data.

31. (Previously Presented) The method of claim 27 further comprising transmitting an electronic message including an address of the hard copy output engine from the second side of the firewall to the first side of the firewall.

32. (Previously Presented) The method of claim 27, wherein the hard copy output engine configuration data designates a website on the first side of the firewall as a contact for the hard copy output engine, wherein the website was not previously designated to the hard copy output engine.

33. (Canceled)

34. (Canceled)

35. (Previously Presented) The method of claim 27 further comprising receiving the electronic message with a web server embedded in the hard copy output engine.

36. (New) The method of claim 1 wherein the hard copy output engine configuration data designates a website on a first side of the firewall as a contact for the hard copy output engine, wherein the website was not previously designated to the hard copy output engine.

37. (New) The method of claim 1 further comprising:

providing input by interacting with a website on the first side of the firewall with a web browser on the second side of the firewall; and

forming the hardcopy output engine configuration data on the first side of the firewall using the input from the second side of the firewall.

38. (New) A method comprising:

forming hard copy output engine configuration data on a first side of a firewall based upon input received from a second side of the firewall; and

transmitting an electronic message including the configuration data through the firewall to a hard copy output engine on the second side of the firewall, wherein the hard copy output engine configuration data designates a website on the first side of the firewall as a contact for the hard copy output engine, wherein the website was not previously designated to the hard copy output engine.